



Attestation of Conformity

No. N8AUK 086019 0052 Rev. 00

Holder of Certificate:

ShenZhen RiHuiDa Power Supply Co., Ltd.

2, 3 & 4F, No. B Building Rihuida Technology Park No. 28 Hongyuan Road, Pingdong Community Pingdi Sub-District Longgang District 518117 ShenZhen PEOPLE'S REPUBLIC OF CHINA

Product:

Adaptors (AC/DC ADAPTOR)

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulations and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.:

64210210181101

Date,

2021-07-15

(Richard Zhu)

Page 1 of 2

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.





Attestation of Conformity

No. N8AUK 086019 0052 Rev. 00

Model(s):

RHD20Wxxxyyyz, RHDaaWxxxyyyB, RHD20W050yyyBS [xxx=030-480 stands for output voltage range 3.0-48.0VDC in step of 0.1V; yyy=010-300 stands for output current range 0.1-3.0A in step of 0.01A; z=S or blank stands for the different type of output, S for USB output type, blank for output cord type; aa=18, 19 or 20 stands for the different shape of enclosure, 18 for vertical enclosure, 19 for square horizontal enclosure, 20 for horizontal enclosure with stripes.]

Parameters:

Rated Input: 100-240VAC, 50/60Hz, 1.5A Rated Output: See below table for details Protection Class: II Degree of Protection: IP20

| Model name | Input rating | Output rating | | |
|---------------------------------|------------------------------|---------------------|-------------------|----------------|
| | | Voltage range (VDC) | Current range (A) | Max. Power (W) |
| RHD20Wxxxyyyz, RHDaaWxxxyyyB | 100-240VAC, 50/60Hz, 1.5A | 3.0-8.9 | 0.1-3.00 | 15.0 |
| | | 9.0-24.0 | 0.1-2.00 | 18.0 |
| | | 24.1-48.0 | 0.1-0.74 | 18.0 |
| RHD20W050yyyBS | | 5.0 | 0.1-3.00 | 15.0 |

Tested according to:

EN 62368-1:2014/A11:2017 BS EN 62368-1:2014/A11:2017

Page 2 of 2

After preparation of the necessary UK regulation technical documentation as well as the UK declaration of conformity the required UKCA marking can be affixed on the product. Other applicable UK regulations have to be observed.