ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

Attestation of Conformity

No. N8A 086019 0032 Rev. 00

Holder of Certificate: **ShenZhen RiHuiDa Power Supply Co., Ltd.**
2, 3 & 4F, No. B Building
Rihuida Technology Park
No. 28 Hongyuan Road, Pingdong Community
Pingdi Sub-District
Longgang District
518117 ShenZhen
PEOPLE'S REPUBLIC OF CHINA

Product: **Battery charger (Battery Charger)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance.
It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 64260100800001

Date, 2020-04-20 (Michael Xu)

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

Attestation of Conformity

No. N8A 086019 0032 Rev. 00

Model(s):

RHDzzWxxxyyy
(zz=10, 20, 30, 50 or 75 indicates rated output power, 10 indicates rated output power up to 10.0W, 20 indicates rated output power above 10.0W and up to 20.0W, 30 indicates rated output power above 20.0W and up to 30.0W, 50 indicates rated output power above 30.0W and up to 50.0W, 75 indicates rated output power above 50.0W and up to 75.2W; xxx=033-410 indicates rated output voltage 3.3-41.0VDC; yyy=001-800 indicates rated output current 0.01-8.00A.)

Parameters:

Rated Input: 100-240VAC, 50/60Hz, 1.5A
Rated Output: See below table for details
Protection Class: II
Degree of Protection: IP20

Model	Output voltage (VDC)	Output current (A)	Max. output power (W)
RHDzzWxxxyyy	3.3-8.5	0.01-8.00	68.0
	8.6-15.0	0.01-8.00	75.2
	15.1-25.0	0.01-4.90	75.0
	25.1-36.0	0.01-2.90	75.0
	36.1-41.0	0.01-2.00	75.0

Tested according to:

EN 60335-1:2012/A2:2019
EN 60335-2-29:2004/A11:2018
EN 62233:2008

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

A4 / 07.17